



Specifications

The start/stop procedure	Works by means of a charging card
Number of connections:	2
Connection:	Socket type 2
Connection value:	From 1x16A up to 3 x63A.
Power output per socket:	0 up to 22 Kw
Protocol:	Mode 3
Positioning:	GPS
Communication:	UMTS / GSM Modem / Controller with RFID-reader
Casing material:	Steel 4 mm/Scales: 3,6mm
Standard Colour:	RAL 6018/RAL 9016
Treatment:	Anti-corrosion treatment and powder coating
Measurements casing (HxDxB):	1400mm x 240mm x 200mm
Weight:	56kg
Norms:	NEN1010/EU/35-IEC: 61851-1 VDE-AR-E 2623-2-2/IE5/IK10
Water resistance:	IP54

Warranty:	Standard: 1 year
(Optional: Warranty Plus)	

ECOTAP Charging Station DUO Type: SLA_K

This car charging station works on three-phase electric power and features car communication technology. It was specifically designed for public places prone to vandalism. Therefore this chargingstation is Vandalism resistant and is Made of 4 mm steel.

Smart Charging

Makes smart charging of electric cars accessible to everyone. Smart Charging means that the available power capacity is used in a "smart" fashion. The charging capacity is always optimally divided among the charging stations in use.

CONTACT

Telephone: +31 (0) 411 210 210
Email: Nicole@ecotap.info
Website: www.ecotap.nl

